SINTS Safety never felt so comfortable

The revolutionary PAPR system from optrel



TH3 certified particle master filter











No fit test necessary





14 h power pack



5 E E WHAT YOU CAN DO

SHISS AIR

Perfect breathing air

Breathing means living. The optrel swiss air respiratory protection system brings clean breathing air into your environment and lets you breathe as freely as you can otherwise only enjoy outdoors in nature.

Many workplaces and public spaces produce pollutants such as smoke, soot particles, particulate matter, nitrogen oxides, ozone or viruses that can enter the lungs through the nose, throat and trachea, causing asthma, chronic cough, bronchitis or other respiratory diseases including lung cancer.

With the optrel swiss air respiratory protection system you enjoy fresh air, completely independent of your activity and your other protective equipment. It makes you independent and free.

WELCOME TO THE SWISS ALPS. WELCOME TO OPTREL SWISS AIR.

Ventilated half mask made of flameretardant material covers mouth and nose area completely. Positive pressure supports breathing and avoids fatigue.

> Shoulder harness for ergonomically perfect weight distribution of the super-light filter system (only 550 g).

The Control Panel operates all functions centrally from the front:

- easy indication of filter and battery status
- stepless regulation of the air flow for maximum working comfort
- Automatic altitude and temperature compensation

TH3 certified 99.8%

swiss air meets the highest requirements for professional respiratory protection systems, the TH3 standard: 99.8% of all harmful particles, aerosols, vapors, smoke or even viruses are reliably filtered out of the breathing air. Infinitely adjustable headband for all sizes from XS to XL.

Y-hose with adjustable neck strap and flexible hose elements guides the air directly into the half mask

optadi

Powerful TH3 filter unit with innovative, ultra-flat design. Lightweight and comfortable to carry, highly efficient in use. Blower unit with automatic air flow calibration and 14h high performance battery for an uninterrupted working day.

> spark protection pre-filter

cover

TH3 particle master filter

Flexible use for numerous types of work

The optrel swiss air respiratory protection system is independent of the helmet or other equipment used and is therefore the most versatile optrel respiratory protection system available.



Medical applications / Health care

Welding / Plasma cutting

optre



Laboratory applications / pharmaceutical industry

Technical data

Protection class	TH3 (EN12941)
Blower unit	
Air flow	Level 1: min. 100 l/min. Level 2: min. 115 l/min. Level 3: min. 130 l/min. All levels with automatic air flow control (levels are adjusted directly on the blower and can be steplessly adjusted via the Control Panel at the front).
Material	PA66 GF30
Fan	high quality motor with ball bearings
Fuse	electronical
Noise	max. 70db (A)
Alarm	Visual (with swiss air control panel) and audible for low / very low battery level, clogged filter, no filter and low air flow. Low battery: alarm frequency 3.0 s (1.5 s on, 1.5 s off) Filter: alarm frequency 0.5 s (0.25 s on, 0.25 s off)
Dimensions	(L x W x H): 250 x 170 x 50 mm
Weight	Blower unit 550 g / Overall system 1,200 g
Control Panel	
Indication and adjustment options	- Overview of filter contamination and battery charge status - stepless air flow control and on/off switch - altitude and temperature compensation
Connection	Operating cable with jack plug and cable protection
Half-mask	
Material	POM, ripstop textile (98% polyester and 2% polyurethanes), flame-retardant Polyurethane foam
Valve	Exhalation valve with silicone membrane
Certificates	
Standards	EN 12941 Europe: TH3; Australia: P3; AS/NZS 1716; EAC TP TC 019/2011
Notified body	CE 1024



Con qualsiasi acquisto di questo prodotto, optrel pianta un albero e neutralizza l'impronta di carbonio del prodotto.





optrel AG industriestrasse 2 CH-9630 wattwil switzerland industrial.optrel.com info@optrel.com Your optrel reseller:



industrial.optrel.com