



3M™ Cubitron™ II Cut and Grind Wheels

3M I.D. Number	3M™ Cubitron™ II Cut and Grind Wheels
Product Description	3M™ Cubitron™ II Cut and Grind Wheels are a Type 27, reinforced resin-bonded wheels containing 3M-patented ceramic Precision Shaped Grain (PSG) mineral. The result of this is a cut and grind wheel that yields a fast cut and extended life superior to that of its competitors. 3M™ Cubitron™ II Cut and Grind Wheels are ideal for mild steel, stainless steel, and nickel alloys.
Mineral	A blend of crushed aluminum oxide and ceramic Precision Shaped Grain (PSG)
Construction	Resin bonded wheels with a triple reinforced construction for added safety and durability; INOX formulation (Fe < 0.1%, S < 0.1%, and Cl < 0.1%) for stainless steel applications
Dimensions	100 mm, 115 mm, 125 mm, 150 mm, 180 mm, and 230 mm diameter x 4.2mm thick
Safety	Always use appropriate PPE and follow safety precautions as instructed in the associated Product Safety Insert. Product Safety Inserts are included with shipped product and are also available on-line through 3M.com.

Products

Euro

<u>Part Number</u>	<u>Dimension</u>
7100213967	100 x 4,2 x 16
7100214038	115 x 4,2 x 22,23
7100214085	125 x 4,2 x 22,23
7100214087	150 x 4,2 x 22,23
7100214088	180 x 4,2 x 22,23
7100214089	230 x 4,2 x 22,23

Japan Specific

<u>Part Number</u>	<u>Dimension</u>
7100214037	100 x 4,2 x 15

IMPORTANT NOTICE TO PURCHASER:

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Abrasive Systems Division
3M Center Building 240-1-01
Saint Paul, MN 55144 USA

1-866-279-1235
www.3M.com/abrasives

3M is a trademark of 3M.
Please recycle. © 3M 2019. All rights reserved.